



Colour Print PU

This soft, stretchable printable heat transfer vinyl features low-temperature application, reducing the risk of scorched garments.

FEATURES

- Semi-gloss finish
- 80 microns
- Recommended for solvent and eco-solvent printer/cutters
- Polyurethane composition with polyester backing
- Use with Colour Print Easy Masking
- Available in 20" by 1, 5, 10, 25 yard rolls

RECOMMENDED FABRICS

- 100% Cotton
- 100% Uncoated Polyester
- Cotton/Poly Blends

Due to the combination of fabrics, weaves, coatings and dyes used in the textile industry, we recommend testing the application before production.





RECOMMENDED INKS

Recommended for use in Eco-Solvent and Solvent based Printer | Cutters.

APPLICATION

1. Preheat your garment for 2-3 seconds
2. Align your design on the garment
3. Heat apply for 15 seconds at 300° F with a medium pressure
4. Peel warm

APPLICATION

-  15 seconds
-  300° F
-  Medium
-  Warm

CARE

- Wait 24 hours before the first wash
- Machine wash warm using mild detergent
- Dry on normal setting
- Do not use bleach
- Do not dry clean

ACCESSORIES

- Weeder
- Cover Sheet
- Flex Heat Easy Masking



All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance conditions not under manufacturer's control. Before using, we recommend testing to determine suitability of the product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product.